

Tender texts

PREFA roof and façade systems (06/2018)

Specifications 02 PREFA façade systems

Title 02.08 PREFA FX.12 façade panel

GENERAL OBSERVATIONS

Author:

PREFA Aluminiumprodukte GmbH
3182 Marktl/Lilienfeld (Austria)

Last updated on 13/07/2017

Performance of the described services is based on PREFA Aluminiumprodukte GmbH's installation and mounting instructions, and on the nationally applicable rules, technical regulations and standards.

The specifications are based on the following documents:

-
-
-

The following specifications were created based on the planning documents made available to us according to the currently applicable rules of sound engineering practice. The tenderer must check the items for feasibility; the quantities must be checked for accuracy with regards to the building, and amended if necessary.

Material waste, loss of material in seam area, small items and fixing material must be taken into account with the items in question. Invoicing is carried out according to on-site measurements.

We strongly recommend visiting the site prior to submitting the tender.

The following are not included in this call for tender: work, façade and safety scaffolding, road barriers, official permits, lightning protectors, neighbouring buildings, balconies and projecting roofs. The customer is responsible for ensuring compliance with building physics and structural engineering requirements.

PREFA Aluminiumprodukte GmbH does not guarantee the completeness of the individual items to perform the services described, or the accuracy of the dimensions of the individual items. The planner must verify all statements and information for correctness, and make any necessary adjustments. This preparatory work for the tender is provided as an advisory service for the planner (e.g. architects).

02.08.1 Façade cladding with PREFA FX.12

Delivery and installation of stainless aluminium façade cladding with PREFA FX.12; including PREFA fixing material (concealed fastening with ring nails, directly attached, 4 per rhomboid façade tile); on solid sheathing or skip sheathing (at least 24 mm thick). The PREFA installation guidelines must be observed.

Installation: from right to left; panels offset by min. 220 mm
Size: 1,400 × 420 mm (3.4 pc./m²), 700 × 420 mm (1.7 pc./m²) — cover
Material thickness: 0.70 mm
Weight: 2.5 kg/m²
Material: aluminium (fully recyclable)
Alloy: EN AW-3005 or EN AW-3105 in accordance with EN 573-3
Front: P.10 or Duragloss 5000 coil coating
Colour:
(Standard according to valid PREFA colour chart)
Reverse: protective paint
Finish: smooth
Class of reaction-to-fire performance: A1 in accordance with EN 13501-1
Environmental Product Declaration in accordance with ISO 14025 and EN 15804: EPD-GDA-20130260-IBG1-DE
Reference service life according to Environmental Product Declaration: ≥ 70 years

0.000 m² UP _____ TP _____

02.08.2 PREFA edge cleat strip

Delivery and installation of PREFA edge cleat strips (with marking); including fixing material and attachment to the PREFA façade cladding. The PREFA installation guidelines must be observed.

Size: 1,800 × 158 mm
Material thickness: 1.0 mm
Material quality: aluminium

0.000 m UP _____ TP _____

02.08.3 Lower connection of PREFA FX.12 façade

Delivery and installation of bottom connection; including fixing material and attachment to façade cladding.

Material thickness: same as the main item
Material quality: same as the main item
Colour: same as the main item

Cover flashing:
Cutting dimension: ... mm
Downstand: ... mm

Insertion profile:
Cutting dimension: 120 mm
Downstand: 3 pc.
Length: 2,000 mm

0.000 m UP _____ TP _____

02.08.4 PREFA drip

Delivery and installation of PREFA drip for lower connection, horizontal separation and top window connection. Including fixing material, joint connector and attachment to the façade cladding.

Cutting dimension: 120 mm
Downstand: 3 pc.
Length: 2,500 mm
Material thickness: same as the main item
Material quality: same as the main item
Colour: same as the main item

0.000 m UP _____ TP _____

02.08.5 Canted channel profile

Delivery and installation of canted channel profiles for wall connection and top connection; including fixing material, sealants and attachment to the PREFA façade cladding.

Cutting dimension: up to 150 mm
Downstand: 3 pc.
Colour: same as the main item
Material thickness: same as the main item
Material quality: same as the main item

0.000 m UP _____ TP _____

02.08.6 Construction of protruding and recessed corners (two parts)

Delivery and installation of protruding and recessed corners (two parts); including fixing material and attachment to the PREFA façade cladding.

Total cutting dimension: up to 250 mm
Downstand: up to 8 pc.
Length: 2,000 mm
Material thickness: same as the main item
Material quality: same as the main item
Colour: same as the main item

0.000 m UP _____ TP _____

02.08.7 Construction of protruding and recessed corners (three parts)

Delivery and installation of protruding and recessed corners (three parts); including fixing material and attachment to the PREFA façade cladding.

Total cutting dimension: up to 450 mm
Downstand: up to 9 pc.
Material thickness: same as the main item
Material quality: same as the main item
Colour: same as the main item

0.000 m UP _____ TP _____

02.08.8 Vertical window/door connection (reveal) made of PREFA flashing strip

Delivery and installation of horizontal window/door connections (lintel) made of PREFA flashing strip. Including fixing material and sealants and attachment to the PREFA façade cladding, window ledge and lintel. Make sure that the thermal insulation is correctly attached to the frame.

Reveal:

Cutting dimension: ... mm

Downstand: ... pc.

Material thickness: same as the main item

Material quality: same as the main item

Colour: same as the main item

Insertion profile:

Cutting dimension: 120 mm

Downstand: 3 pc.

Length: 2,000 mm

0.000 m

UP _____ TP _____

02.08.9 Horizontal window/door connection (lintel) made of PREFA flashing strip

Delivery and installation of horizontal window/door connections (lintel) made of PREFA flashing strip. Including fixing material and sealants and attachment to the PREFA façade cladding and window reveal. Make sure that the thermal insulation is correctly attached to the frame.

Lintel:

Cutting dimension: ... mm

Downstand: ... pc.

Material thickness: same as the main item

Material quality: same as the main item

Colour: same as the main item

Insertion profile:

Cutting dimension: 120 mm

Downstand: 3 pc.

Length: 2,000 mm

0.000 m

UP _____ TP _____

02.08.10 Window ledges made of PREFA flashing strip

Delivery and installation of window ledges made of PREFA flashing strip; including fixing material and production of lateral connections.

Window ledge:

Cutting dimension: ... mm

Downstand: 3 pc.

Material thickness: same as the main item

Flashing strip:

Cutting dimension: ... mm

Downstand: 1 pc.

Material thickness: 1.00 mm

0.000 m UP _____ TP _____

02.08.11 Roof parapet flashing made of PREFA flashing strip

Delivery and installation of roof parapet flashing made of PREFA flashing strip; including cleat strips on both sides and fixing material. The individual elements must be prepared in lengths of up to 3,000 mm max. according to the cut. Connection types: standing seam, hook seam, coulisseau or corrugated metal sheathing.

Cutting dimension: ... mm
Downstand: 4 pc.
Material quality: aluminium
Alloy: AlMn1Mg0.5, H41
Material thickness: 1.00 mm
Colour: same as the main item

0.000 m UP _____ TP _____

02.08.12 Production of penetrations

Production of penetrations for support profile (e.g. billboards, ventilations, etc.) in the PREFA façade cladding, including support structure or auxiliary structure, fixing material, sealants and attachment to the PREFA façade cladding.

Opening size: ... x ... mm

0.000 pc. UP _____ TP _____

02.08.13 PREFA perforated plate for ventilated façades

Delivery and installation of PREFA perforated plates with perforations for aeration and ventilation, and to prevent insects and birds from getting into the ventilated channel; including fixing material.

Cutting dimension: ... mm
Downstand: as required
Material: aluminium
Alloy: EN AW-3005
Material thickness: 0.70 mm
Round perforations: ø 5 mm

0.000 m UP _____ TP _____

02.08.14 Skilled worker hourly rate

Skilled worker hourly rate

0.000 h UP _____ TP _____

02.08.15 Assistant hourly rate

Assistant hourly rate

0.000 h UP _____ TP _____

Title 02.08 PREFA FX.12 façade panel TP _____

Summary

Title 02.08 PREFA FX.12 façade panel

TP _____

Specifications 02 PREFA façade systems

TP _____